



Proceq Ground Penetrating Radars


GP8800

Concrete inspections and structural imaging with SFCW ground penetrating radar technology now fits at the palm of your hand



Performance

Superior depth and clarity of data thanks to the unique Swiss Made radar technology with all the frequencies you'll ever need. Immediate insights with 3D and Augmented Reality.



Versatility

Inspect with ease of use, from the tightest spots to the tallest walls to the longest streets. Superior ergonomics to tackle any challenge with comfort, without cables.



Productivity

A mobile app that lets you annotate measurements with voice, photos and comments. Generate reports and share them instantly. Access your data from anywhere, anytime.



Proceq GPR App

Tech Specs

Measurement modes	Line Scan, Superline Scan ¹ Area Scan (with Flexible Grid up to 16m ² / 172 ft ² , or up to 100m ² / 1076ft ²) ¹ *
Review modes	Line scan (B-scan), Superline scan ¹ A-scan (incl. envelope) Migrated view Non-migrated view Split view ¹ Time-Slice view ³ 3D view AR
Advanced visualization	Time-Slice view Pro 3D view Augmented Reality (AR)
Reporting	Workspace integration Automatic Logbook SEG-Y export Instant report generation Share via URL
Export formats	JPG PNG DOCX SEGY HTML
Display Unit Specs*	Latest Apple® iPad recommended (iPad with iOS 13.6 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID
Display Unit Sensors*	LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer Built-in GPS/GNSS

[Proceq GPR App | Info & compatibility](#)

1. GP8100 only; 2. GP8000 & GP8800 only; 3. GP8000 & GP8100 only

* Depending on iPad model









Instrument

Tech Specs

Radar technology	Stepped-frequency continuous-wave (SFCW) GPR
Modulated frequency range	400 – 6000 MHz
Penetration depth	65 cm / 25.6 in
Battery	1x Removeable Li-ion Battery Pack 2x Removeable Flight-safe, removable pack, 4x AA (NiMH)
Dimensions	8.9 x 8.9 x 7.6 cm 3.5 x 3.5 x 3 in
Weight	487 g / 17.2 oz (excl. battery pack)
Ground clearance	0 cm
Antennas	1
Antenna distance to edge	4.5 cm / 1.77 in
Special features	Wireless wheel, reconfigurable at any time without tools. Cross-polarization (trailing and side-car configurations) USB-C tethering to battery pack/power bank
Connections	WiFi and USBC to display unit
Autonomy	Li-ion Battery Pack: Up to 8h Battery Pack (4xAA NiMH): Up to 2.5h Power bank (not included): Up to 8h



Our Accessories

Image	PartNumber	Description
	39380010	Telescopic rod kit for Proceq GPR instruments including the universal tablet holder UTH100...
	79330235	Universal tablet holder for direct mounting on Proceq GPR 8000/8100 and Pundit PD8050...
	79330345	Chest harness kit for hands free operation of all iPad app based instruments:...
	91011110	Durable carry strap
	39335130	Scan concrete for up to 8 hours on a single charge. Recharge easily with any USB-C port.
	39330076	Adapted for the new GP8800 Li-on battery pack

Standards & Guidelines	Description
ACI 228.2R.98	
ASTM D4748-10	
ASTM D6087-08	
ASTM D6432-11	
EN 302066 - ETSI	
NCHRP Synesis 255	
SHRP H-672	
SHRP S-300	
SHRP S-325	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.
www.screeningeagle.com

Request a
quote



Machine translated & automatically generated (English version prevails): 27.08.2025
 Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.

