



## Automatic film applicators

# ZAA2300

### Automatic Film Applicator



#### Ease of use

Design reduced to what really matters. Get your work done as you expect. Clamp your specimen securely, use the applicators of your choice, set the drawing range and speed -  
START




#### Accuracy

Swiss precision ensures that the applicator is running with the same speed and a super smooth movement— again and again. This ensures reproducible and perfect film surfaces



#### Durability

With an unprecedented live time and requiring almost no maintenance this instrument represents Swiss quality at its best



## Instrument Tech Specs

Application length	Application length: up to 400 mm (15.75")
Application width	Application width: up to 300 mm (11.81")
Weight	20 kg (44.1 lbs) glass plate only: 6.4 kg (14.1 lbs)
Battery	Power supply: 100 V - 240 V, 50 Hz - 60 Hz
Operating Temperature	Ambient conditions for the operation: Temperature range: 5°C to +45°C (41 °F to 113 °F) Relative humidity: 20% to 80%, no condensation
Temperature range	Ambient conditions for operation: 5°C to +45°C (41 °F to 113 °F)
Relative humidity	20% to 80%, no condensation
Drawing speed	ZAA2300 0-99 mm/s ZAA2300.F 0-247.5 mm/s ZAA2300.FF 0-495 mm/s
Tolerance of drawing speed	ZAA2300 0-90 mm/s ZAA2300.F 0-225mm/s ±1%   >90 mm/s ±3% ZAA2300.FF 0-450mm/s ±1%   >450 mm/s ±3%
Resolution of drawing speed	ZAA2300 1 mm/s ZAA2300.F 2.5 mm/s ZAA2300.FF 5 mm/s

Standards & Guidelines	Description
ASTM D1640 (Depending on accessory)	
ASTM D4748-10	
ASTM D823 (Depending on accessory)	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

Request a quote



Machine translated & automatically generated (English version prevails): 03.04.2025  
 Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.

