



Zehntner Gloss
ZGM 1130

Touchscreen Display for all Gloss Ranges




Accuracy

Stable and reliable results..



Ease of use

Features single, multiple and even continuous scan gloss measurements.



Versatility

Versatile measuring and data analysis software.



Instrument Tech Specs

PC Software	Screening Eagle Workspace
Display	2.4" touchscreen
Memory	1 million measurements
Measurement Modes	Sensor adaption V(λ)
Measuring Geometries	1-angle: 60° 2-angle: 20°, 60° 3-angle: 20°, 60°, 85°
Measuring Range	0 - 2'000 GU
Measuring Accuracy	0 - 199.9 GU: $\pm 0.1 \%$ 200 - 2'000 GU: $\pm 0.2 \%$
Weight	420 g (0.93 lbs)
Battery	Lithium Ion

Standards & Guidelines	Description
ASTM D2457	
ASTM D4039	
ASTM D523	
BS 3900-D6	
DIN 67530	
EN 13300	
ISO 2813	
JIS Z 8741	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.
www.screeningeagle.com

Request a
quote



Machine translated & automatically generated (English version prevails): 27.08.2025
 Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.

