



Proceq 涂层和薄膜测试  
**Proceq ZHT 2093**

---

便携式硬度计

---

**便于使用**

易于处理

**高性能**

精准定位

**多用性**

轻松读取不同的摩擦力

## 仪器 技术规格

尺寸	0.5 mm [0.02"]、0.75 mm [0.03"] 和 1.0 mm [0.04"] 尖端可用
重量	73 克 [0.16 磅]
	3 压力弹簧
	白色：力：0 - 3N (0 - 0.3 kg)，分辨率：10 g [0.02lbs]
特殊功能	
	蓝色：力：0 - 10N (0 - 1 kg)，分辨率：50 g [0.11lbs]
	红色：力：0 - 20N (0 - 2 kg)，分辨率：100 g [0.22lbs]



## 我们的配件

Image	PartNumber	Description
	43010915	1.0 mm [0.04"] 尖端 (43010915) 配件
	43010916	0.5 mm [0.02"] 尖端 (43010916) 配件
	43010929	用于耐刮擦和耐擦伤测试的适配器 (43010929) 附件

Standards & Guidelines	Description
DIN 55656	
DIN SPEC 91064	
Volkswagen TL 226	

SWISS  MADE



我们的业务遍及 100 多个国家，为世界各地的检验员和工程师提供最全面的 InspectionTech 解决方案，结合直观的软件和瑞士制造的传感器。  
[www.screeningeagle.com](http://www.screeningeagle.com)

请求报价



